

New!

ProSport 1.5 Amp

Fully Automatic Battery Maintainer & Charger

Ideal for personal watercraft, recreational ski and wake boats, ATV's, tractors and more.

Our newest generation ProSport 1.5 Amp fully automatic maintainer is an innovative multi-use charger designed for maximum utility. Concealed mounting holes allow the ProSport 1.5 to be installed on-board or to be used as a portable, with rear die cut foam resting pad. Ring terminal and DC clamp quick connect cable assemblies included.

Our marine grade design is weatherproof, water resistant to IP 65 and can be used in all fresh and salt water outdoor and indoor applications as needed.

Designed to keep 12 volt batteries fully charged during short or long term storage periods, ProSport's Energy Saver mode will monitor and auto maintain a battery when needed to maintain a full state of charge. ProSport 1.5 significantly reduces AC Power consumption, lowers operating costs and maximizes reserve power performance.

- Fully automatic energy saving design
- Multi-use design, easily configures for on-board or portable use
- Concealed mounting holes & die cut foam resting pad for portable use
- Expanded LED display for Power, Charging and Auto Maintain status
- Maintain 12 volt lead acid (sealed & vented) batteries up to 150 amp hours
- Quick connect DC clamp & ring terminal cable assemblies
- Weatherproof and water resistant to IP65
- Built-in safety with reverse polarity, short circuit, temperature and ignition protection
- Pre-wired for easy installation
- 3 year warranty



Concealed Mounting

Expanded LED Status Center

Portable Foam Resting Pad

Included DC Cable Assemblies

Certified to:
UL STD. 1236
CSA STD. C22.2 No. 107.2
FCC Class B



Designed and Constructed to: ABYC A-31



model	part no.	battery type	amps	no. of batteries	charging	auto maintain (up to 150 AH)	AC input	cable length	AC plug	dimensions	weight
ProSport 1.5 Fully Automatic Battery Maintainer & Charger	44001	12 VDC lead acid (sealed & vented)	1.5	1	small batteries up to 40 amp hours	monitored float range 12.9 VDC to 13.4 VDC	120 VAC +/- 10% 60 Hz	6'	3 wire NEMA 5-15P	5" x 5.75" x 1.97"	2.3 lbs